

**MOTUL MULTI CVTF**

**Continuously Variable Transmission (CVT) Fluid fitted with chain or belt Technosynthese®**

**TYPE OF USE**

High performance synthetic Technosynthese® fluid specially engineered for Continuously Variable Transmission (CVT) gearbox type.

Suitable for use in a wide range of vehicles fitted with CVT gearboxes using either chain/pulleys or belt/pulleys design.

Especially suitable for vehicles from American car makers GM, FORD, CHRYSLER,..., Asian car makers HONDA, HYUNDAI, KIA, LEXUS, INFINITI, MITSUBISHI, NISSAN, SUBARU, TOYOTA,... or European car makers AUDI, BMW, CITROËN, MERCEDES, PEUGEOT, RENAULT, ...

Attention, not recommended for CVT unit fitting hybrid vehicles. Before use always refer to the owner manual or hand-book of the vehicle.

**PERFORMANCES**

MOTUL MULTI CVTF is a high tech multi vehicles CVT fluid suitable for a wide range of CVT-equipped passenger cars, including belt-CVT and chain-CVT design.

Thanks to its exclusive and dedicated synthetic formula, MULTI CVTF:

- Allows fuel economy for cars fitted with CVT automatic gearboxes by providing optimum metal-to-metal friction.
- Provides high anti-shudder performance to avoid engine vibrations for increased comfort.
- Protects gears that are more and more numerous, compact and heavily loaded.
- Gives superior automatic transmission response through smooth shift feel and reduced shift time lag.
- Improves CVT reaction at cold temperature.
- Extends life time duration due to high shear stability at hot temperature and high oxidation resistance.
- Increases wear protection of belt, chain and pulleys.
- Anti-corrosion, anti-foam.

**RECOMMENDATIONS**

Can be mixed only with similar lubricants.

Oil change: according to manufacturer's recommendations and adapt according to your own use.



## MOTUL MULTI CVTF

Continuously Variable Transmission (CVT) Fluid fitted with chain or belt  
Technosynthese®

Not recommended for CVT unit fitting hybrid vehicles.

Before use always refer to the owner manual or handbook of the vehicle.

### PROPERTIES

Color	Visual	Blue
Density at 20°C (68°F)	ASTM D1298	0.852
Viscosity at 40°C (104°F)	ASTM D445	34.3 mm <sup>2</sup> /s
Viscosity at 100°C (212°F)	ASTM D445	7.2 mm <sup>2</sup> /s
Viscosity Index	ASTM D2270	180.0
Flash point	ASTM D92	210.0 °C / 410.0 °F

Continuously Variable Transmission (CVT) Fluid fitted with chain or belt  
Technosynthese®

OE PERFORMANCES	
<b>AUDI</b>	G 052 180, G 052 516, Multitronic, TL 52 116, TL 52 180, TL 52 516
<b>BMW</b>	83 22 0 136 376, 83 22 0 429 154, EZL 799, EZL 799 A
<b>CHERY</b>	CVT
<b>CHRYSLER</b>	CVTF+4, NS-2
<b>CITROËN</b>	9735 EF, Elfmatic CVT, Elfmatic CVT MV
<b>DAIHATSU</b>	AMMIX CVTF DFE, AMMIX CVT Fluid DC, AMMIX CVT Fluid DFE, CVTF 3320, CVT Fluid DFC, Fluid TC
<b>DODGE</b>	05191184AA, CVTF+4, NS-2
<b>DS (CAPSA)</b>	9735 EF, Elfmatic CVT, Elfmatic CVT MV
<b>FIAT</b>	Tutela Car CVT N.G
<b>FORD</b>	CVT23, CVT30, MERCON C, WSS-M2C928-A, WSS-M2C933-A, XT-7QCFT
<b>GENERAL MOTORS</b>	1940713, 1940714, CVTF I-Green2, DEX-CVT, HP CVTF 95529854, VT40
<b>HONDA</b>	08200-9006, 08200-HCF-2, 0826099905HE, 087009006, HMMF (Honda Multi Matic Fluid) for CVT models only, without wet starting clutch, CVT-F, Genuine CVT Fluid, HCF-2, Z-1 (CVT models only, without starting clutch, not for Honda Jazz & Fit MY 2001-2007)
<b>HYUNDAI</b>	CVT-1, Genuine CVTF, SP-CVT 1, SP III (CVT models only)
<b>INFINITI</b>	NS-1, NS-2, NS-3
<b>JEEP</b>	05191184AA, CVTF+4, NS-2, VTF
<b>KIA</b>	CVT-1, SP-CVT 1, SP III (CVT models only)
<b>LEXUS</b>	CVTF 3320, CVT FE, Fluid FE, Fluid TC
<b>LIFAN</b>	CVT
<b>MAZDA</b>	CVTF 3320, JWS 3320
<b>MERCEDES-BENZ</b>	A 001 989 46 03, MB 236.20
<b>MG</b>	EM-CVTF
<b>MINI</b>	83 22 0 136 376, 83 22 0 429 154, COOPER EZL 799 A, EZL 799, ZF CVT V1
<b>MITSUBISHI</b>	CVTF ECO J4, Dia Queen CVTF-J1 (MMC Diaqueen CVT Fluid J1), Dia Queen CVTF-J4, Dia Queen CVTF-J4+ (MMC Diaqueen CVT Fluid J4 and J4+), MZ313973, SP III (CVT models only)
<b>NISSAN</b>	999MP-NS200P, KTF-1, N-CVT, NS-1, NS-2, NS-2V, NS-3
<b>OPEL</b>	7-speed CVT, HP CVTF 95529854, VT40
<b>PEUGEOT</b>	9735 EF, Elfmatic CVT, Elfmatic CVT MV
<b>RENAULT</b>	CVT CK/SK/FK, Elfmatic CVT, Elfmatic CVT MV
<b>ROVER</b>	EM-CVTF, Unipart Transmatic ATF
<b>SATURN</b>	22688912, DEX-CVT
<b>SEAT</b>	G 052 180, G 052 516

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com

**Continuously Variable Transmission (CVT) Fluid fitted with chain or belt  
Technosynthese®**

<b>SUBARU</b>	CV30, CVT III Fluid, CVT TR580, CVT TR690, ECVT, High Torque CVT, High Torque CVTF-LV, iCVTF, i-CVTF FG, K0421Y0700, K0425Y0710, K0425Y0711, Lineartronic chain CVT 3 Fluid, Lineartronic chain CVT and CVT II Fluid, Lineartronic CVTF, Lineartronic High Torque (HT) CVT Fluid, Lineartronic II, NS-2, SOA748V0300
<b>SUZUKI</b>	CVTF 3320, CVTF 4401, CVTF TC, CVT Green 1, CVT Green 1V, CVT Green 2, NS-2
<b>TOYOTA</b>	CVTF 3320, CVTF FE, TC
<b>VAUXHALL</b>	7-speed CVT, HP CVTF 95529854, VT40
<b>VOLVO</b>	CVTF 4959
<b>VW</b>	G 052 180, G 052 516
<b>ZOTYE</b>	RDCF01, RDCF02, CVTs
<b>PRODUCTS</b>	
<b>ELF</b>	matic CVT, matic CVT MV
<b>ESSO</b>	EZL 799, FN1975
<b>FUJIYUKO</b>	i-CVTF FG
<b>IDEMITSU</b>	CVTF-EX1
<b>MOBIL</b>	CVTF 3320
<b>MOPAR PARTS</b>	CVTF+4, CVTplus4
<b>PETRONAS LUBRICANTS</b>	Tutela Car CVT N.G
<b>PSA Groupe</b>	9735 EF, Elfmatic CVT, Elfmatic CVT MV
<b>PUNCH</b>	CVTF-EX1
<b>SHELL</b>	Green 1V

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br\>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

05/22

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - www.motul.com